

Modifications to ECE/TRANS/WP.29/GRSP/2025/19*

I. Proposal

Title, amend to read:

Uniform provisions concerning the approval of vehicles with regard to the protection of the occupants, **fuel system integrity and protection against electrical shock** in the event of a frontal collision

Insert a new paragraph 0, to read:

“0. Introduction

- 0.1. For supplement 2 to the 05 series of amendments:
- 0.1.1. The Regulation is amended to account for vehicles of category X¹. Vehicles of category Y¹ are not in the scope of this Regulation.
- 0.1.2. The Regulation was originally drafted for vehicles with driver and manual driving controls. It is the intention of this ~~new~~ amendment to keep the spirit of the regulation and to extend its application to vehicles without driver and without manual driving controls inside the vehicle. In the absence of driver/manual driving controls in the vehicle, provisions related to them shall not be taken into account if not already covered by this amendment.
- 0.1.3. In case of vehicles equipped with an Automated Driving System (ADS)¹ other than vehicles of category ~~ies~~ X ~~and Y~~, in the manual driving mode no special provisions or exemptions apply. In a mode where an ADS feature is active the relevant ADS requirements apply.”

Paragraph 1., amend to read:

- “1. Scope

This Regulation applies to vehicles of category M₁¹ of a total permissible mass not exceeding 3,500 kg and to vehicles of category N₁ of a total permissible mass not exceeding 2,500 kg; other vehicles may be approved at the request of the manufacturer.

This Regulation does not apply to vehicles of category Y.”

Paragraph 1., footnote 1, amend to read:

- “¹ As defined in the Consolidated Resolution on the Construction of Vehicles (R.E.3.), document ECE/TRANS/WP.29/78/Rev.78, para. 2 - <https://unece.org/transport/vehicle-regulations/wp29/resolutions>”

Paragraph 2.3., amend to read:

- “2.3. “*Vehicle width*” means the distance between two planes parallel to the longitudinal median plane (of the vehicle) and touching the vehicle on either side of the said plane but excluding the external devices for indirect vision, side marker lamps, tyre pressure indicators, direction indicator lamps, position lamps, **sensors for Advanced Driver Assistance Systems, sensors for Automated Driving Systems**, flexible mud-guards and the deflected part of the tyre side-walls immediately above the point of contact with the ground.”

Paragraph 2.6. (b), amend to read:

- “(b) The structure, dimensions, lines and materials of the part of the vehicle forward of the transverse plane through the “R” point of the driver’s seat; **for vehicles**

* Proposal for supplement 2 to the 05 series of amendments to UN Regulation No. 94 (Frontal collision protection)

of category X, the "R" point of the most forward **outboard** passenger seat shall be taken instead of the R-point of the driver's seat."

Paragraph 3.1., amend to read:

"3.1. The application for approval of a vehicle type with regard to the protection of the occupants of the front seats in the event of a frontal collision (offset deformable barrier test), **with regard to the fuel system integrity and with regard to the protection against electrical shock** shall be submitted by the vehicle manufacturer or by his duly accredited representative."

Paragraph 4.4.1 footnote 2, amend to read:

² The distinguishing numbers of the Contracting Parties to the 1958 Agreement are reproduced in Annex 3 to the Consolidated Resolution on the Construction of Vehicles (R.E.3), document ECE/TRANS/WP.29/78/Rev.78, Annex 3 - <https://unece.org/transport/vehicle-regulations/wp29/resolutions>"

Paragraph 5.2.2., amend to read:

"5.2.2. Following the test the residual steering wheel displacement, when measured at the centre of the steering wheel hub, shall not exceed 80 mm in the upwards vertical direction and 100 mm in the rearward horizontal direction.

This paragraph does not apply to vehicles without manual driving controls inside the vehicle."

Paragraph 5.2.3.1., amend to read:

"5.2.3.1. In the case of automatically activated door locking systems which are installed optionally and/or which can be de-activated by the driver **or by the ADS,** ~~This~~ this requirement shall be verified by using one of the following two test procedures, at the choice of the manufacturer:"

Paragraph 5.2.4.2., amend to read:

"5.2.4.2. In the case of vehicles equipped with automatically activated door locking systems which are installed optionally and/or which can be de-activated by the driver **or by the ADS,** ~~This~~ this requirement shall be verified by using one of the following two test procedures, at the choice of the manufacturer:"

Paragraphs 5.3.1. and 5.3.2., after (b), add a new paragraph to read:

" For vehicles of category X, the "R" point of the most forward passenger seat shall be taken instead of the R-point of the driver's seat."

Paragraph 6.1., amend to read:

"6.1. For a vehicle fitted with airbag assemblies intended to protect ~~the driver and occupants other than the driver~~, compliance with paragraphs 8.1.8. to 8.1.9. of ~~UN Regulation No. 16 as amended by the 08 series of amendments,~~ **or with paragraphs 8.1.9. to 8.1.10. of UN Regulation No. 16 as amended by the 09 series of amendments or with paragraphs 5.1.9. to 5.1.10. of UN Regulation No. 173 original series,** shall be demonstrated as from 1 September 2020 for new vehicle types. Before this date the relevant requirements of the preceding series of amendments apply."

Annex 1, amend to read:

"...

Concerning²: Approval granted

Approval extended

Approval refused

Approval withdrawn

Production definitively discontinued

of a vehicle type with regard to the protection of the occupants, **fuel system integrity and protection against electrical shock** in the event of a frontal collision, pursuant to Regulation No. 94

...

Annex 2, model A, paragraph under the figure, amend to read:

“ The above approval mark affixed to a vehicle shows that the vehicle type concerned has, with regard to the protection of the occupants, **fuel system integrity and protection against electrical shock** in the event of a frontal collision, been approved in the Netherlands (E 4) pursuant to UN Regulation No. 94 under approval number 051424. The approval number indicates that the approval was granted in accordance with the requirements of UN Regulation No. 94 as amended by the 05 series of amendments.”

Annex 3, paragraph 1.3., amend to read:

“1.3. Orientation of the barrier

The orientation of the barrier is such that the first contact of the vehicle with the barrier is on the steering-column side. Where there is a choice between carrying out the test with a right-hand or left-hand drive vehicle, the test shall be carried out with the less favourable hand of drive as determined by the Technical Service responsible for the tests.

In case of vehicles of category X, the manufacturer shall propose the tested side. The manufacturer shall provide the authority responsible for approval ~~with to the Technical Service~~ information regarding the ~~compatibility of performances of in comparison with~~ the proposed side in comparison with the opposite side. The Technical Service, ~~if concerned as to the construction of the vehicle, shall will~~ decide to have the test performed on the side considered to be the least favourable.”

Annex 3, paragraph 1.4.3.5.2., amend to read:

“1.4.3.5.2. In the case of vehicles equipped with an automatically activated door locking system that is installed optionally and/or which can be de-activated by the driver or by the ADS, one of the following two procedures shall be used at the choice of the manufacturer:”

Annex 3, paragraph 1.4.3.11.1., amend to read:

1.4.3.11.1. Position of front seats

Seats adjustable longitudinally shall be placed so that their "H" point, determined in accordance with the procedure set out in annex 6 is in the middle position of travel or in the nearest locking position thereto, and at the height position defined by the manufacturer (if independently adjustable for height). In the case of a bench seat, the reference shall be to the "H" point of the driver's place.

For vehicles of category X, the "H" point of the most forward outboard passenger's place shall be taken instead of the H-point of the driver's place.

Annex 5, paragraph 1.2.2., amend to read:

~~“1.2.2. Outer passenger~~

~~The plane of symmetry of the dummy shall be symmetrical with that of the driver dummy relative to the longitudinal median plane of the vehicle. In the absence of a driver dummy, the plane of symmetry of the dummy shall be symmetrical with that of the other passenger dummy relative to the longitudinal median plane of the vehicle. If the seating position is determined by the shape of the bench, such seat shall be regarded as a separate seat.”~~

Annex 5, insert new paragraph 1.2.3., to read:

“1.2.3. Outer passengers for vehicles of category X

For vehicles of category X, the plane of symmetry of the dummies shall be vertical and parallel to the vehicle's longitudinal centreline using the Y-coordinate of the R-points as defined by the manufacturer. If the seating position is determined by the shape of the bench, such seat shall be regarded as a separate seat.”

Annex 5, insert new paragraph 2.2.3., to read:

“2.2.3. For vehicles of category X, the passengers' upper arms shall be in contact with the seat back and the sides of the torso.”

Annex 5, insert new paragraph 2.3.2., to read:

“2.3.2. For vehicles of category X, the palms of the passengers' test dummies shall be in contact with the outside of the thighs. The little finger shall be in contact with the seat cushion.”

Annex 5, paragraph 2.4.1., amend to read:

“2.4.1. In vehicles equipped with bench seats, the upper torso of the driver and passenger test dummies shall rest against the seat back. The midsagittal plane of the driver dummy shall be vertical and parallel to the vehicle's longitudinal centreline, and pass through the centre of the steering wheel rim. The midsagittal plane of the passenger dummy shall be vertical and parallel to the vehicle's longitudinal centreline and the same distance from the vehicle's longitudinal centreline as the midsagittal plane of the driver dummy.

For vehicles of category X, In the absence of a driver's seat, the midsagittal plane of the passenger dummies shall be vertical and parallel to the vehicle's longitudinal centreline using the Y-coordinate of the R-point as defined by the manufacturer.”

Annex 5, paragraph 2.4.2., amend to read:

“2.4.2. In vehicles equipped with individual seats, the upper torso of the driver and passenger test dummies shall rest against the seat back. The midsagittal plane of the driver and the passenger dummy shall be vertical and shall coincide with the longitudinal centreline of the individual seat. **In the absence of a driver's seat, the midsagittal plane of the passenger dummies shall be vertical and coincide with the longitudinal centreline of the individual seat.”**

Annex 5, insert new paragraph 2.6.3., to read:

“2.6.3. For vehicles of category X, the heels of both feet of the passenger test dummies shall be placed as far forward as possible and shall rest on the floor pan. Both feet shall be positioned as flat as possible on the toe board. The longitudinal centerline of the feet shall be placed as parallel as possible to the longitudinal centerline of the vehicle.”

II. Justification

See paragraph 0. in the proposal.
